



Bridge Induction Hob

HI1995G

General description

HI1995G

Main colour: Black ceramic glass

Connected load: 11100 W

Product dimensions (HxWxD): 5 × 90,4 × 52,2 cm

Real Bridge™ induction, Chef function, Auto pan detection, Pause function



**Real
Bridge™
induction**



**Chef
function**



**Auto pan
detection**



**Pause
function**

Construction & Performance

- Connected load: 11100 W
- All heating elements (number of): 6
- 6 induction heating zones Left front: Ø 21×18 cm, 3,7 kW, 120 mm (Minimum detectable pot size), Middle front: Ø 21×18 cm, 3,7 kW, 120 mm (Minimum detectable pot size), Right front: Ø 21×18 cm, 3,7 kW, 120 mm (Minimum detectable pot size), Left rear: Ø 21×18 cm, 3,7 kW, 120 mm (Minimum detectable pot size), Middle rear: Ø 21×18 cm, 3,7 kW, 120 mm (Minimum detectable pot size), Right rear: Ø 21×18 cm, 3,7 kW, 120 mm (Minimum detectable pot size)

Interaction & Control

- Touch control

Programs

- Auto programs: Yes

Design & integration

- Niche dimensions (HxWxD): 4,3 × 86 × 49 cm
- Air gap: 40 mm

Technical data

- Connected load: 11100 W
- Frequency: 50 Hz

Dimensions

- Product dimensions (HxWxD): 5 × 90,4 × 52,2 cm
- Net weight: 16,3 kg

Logistic information

- Dimensions of packed product (HxWxD): 13 × 106 × 60 cm
- Gross weight: 18,5 kg
- Product code: 10037
- EAN code: 3838942353178

