



# HI1975G

## Induction hob

### General description

HI1975G  
Main colour: Black ceramic glass  
Connected load: 11100 W  
Product dimensions (HxWxD): 4,3 × 90,4 × 52,2 cm  
Real Bridge™ induction, Auto pan detection, Pause function



**Real Bridge™  
induction**



**Auto pan detection**



**Pause function**

### Construction & Performance

- Connected load: 11100 W
- Energy consumption in standby mode: 0,5 W
- Middle front: 3,7 kW, 120 mm (Minimum detectable pot size), Right front: 3,7 kW, 120 mm (Minimum detectable pot size), Middle rear: 3,7 kW, 120 mm (Minimum detectable pot size), Right rear: 3,7 kW, 120 mm (Minimum detectable pot size), Left: Ø 26 cm, 5,5 kW, 120 mm (Minimum detectable pot size)

### Interaction & Control

- SmartControl

### Programs

- Auto programs: Yes

### Design & integration

- Aluminium hob edges
- Niche dimensions (HxWxD): 5,3 × 86 × 49 cm
- Air gap: 40 mm

### Technical data

- Connected load: 11100 W
- Frequency: 50-60 Hz

### Dimensions

- Product dimensions (HxWxD): 4,3 × 90,4 × 52,2 cm
- Net weight: 14,7 kg

### Logistic information

- Dimensions of packed product (HxWxD): 14 × 107 × 61 cm
- Gross weight: 16,8 kg
- Product code: 463150
- EAN code: 3838942581090

