



# HI1655M

## Induction hob

### General description

HI1655M  
Main colour: Black mat  
Connected load: 7400 W  
Product dimensions (HxWxD): 5,2 × 64,4 × 52,2 cm  
Real Bridge™ induction, Auto pan detection, Pause function



Real Bridge™  
induction



Auto pan detection



Pause function

### Construction & Performance

- Connected load: 7400 W
- Energy consumption in standby mode: 0,5 W
- All heating elements (number of): 4
- Power boost
- 4 induction heating zones Left front: Ø 19×22 cm, 3700 MJ/h, 120 mm (Minimum detectable pot size), Right front: Ø 19×22 cm, 3700 MJ/h, 120 mm (Minimum detectable pot size), Left rear: Ø 19×22 cm, 3700 MJ/h, 120 mm (Minimum detectable pot size), Right rear: Ø 19×22 cm, 3700 MJ/h, 120 mm (Minimum detectable pot size)

### Interaction & Control

- SmartControl

### Programs

- Auto programs: Yes

### Design & integration

- Aluminium hob edges
- Niche dimensions (HxWxD): 4,8 × 56 × 49 cm
- Air gap: 40 mm

### Safety & Maintenance

- Residual heat indicator

### Technical data

- Connected load: 7400 W
- Frequency: 50-60 Hz

### Dimensions

- Product dimensions (HxWxD): 5,2 × 64,4 × 52,2 cm
- Net weight: 11 kg

### Logistic information

- Dimensions of packed product (HxWxD): 14,5 × 77 × 61 cm
- Gross weight: 12,9 kg
- Product code: 467598
- EAN code: 3838942760327

