



HI1994M

Induction hob

General description

HI1994M
Main colour: Black ceramic glass
Connected load: 11100 W
Product dimensions (HxWxD): 4,3 × 90,4 × 52,2 cm
Real Bridge™ induction, Pan detection, Pause function



**Real Bridge™
induction**



Pan detection



Pause function

Construction & Performance

- Cooktop material: Glass - ceramic
- Connected load: 11100 W
- Energy consumption in standby mode: 0,5 W
- All heating elements (number of): 5
- Power boost
- 5 induction heating zones Left front: Ø 19×22 cm, 2,3/3,7 kW, 120 mm (Minimum detectable pot size), Right front: Ø 19×22 cm, 2,3/3,7 kW, 120 mm (Minimum detectable pot size), Left rear: Ø 19×22 cm, 2,3/3,7 kW, 120 mm (Minimum detectable pot size), Middle rear: Ø 26/18 cm, 3,7/5,5 kW, 120 mm (Minimum detectable pot size), Right rear: Ø 19×22 cm, 2,3/3,7 kW, 120 mm (Minimum detectable pot size)

Interaction & Control

- Touch control

Programs

- Auto programs: Yes

Design & integration

- Aluminium hob edges
- Niche dimensions (HxWxD): 5,3 × 86 × 49 cm
- Air gap: 40 mm

Safety & Maintenance

- Residual heat indicator

Technical data

- Connected load: 11100 W
- Frequency: 50-60 Hz

Dimensions

- Product dimensions (HxWxD): 4,3 × 90,4 × 52,2 cm
- Net weight: 13,5 kg

Logistic information

- Dimensions of packed product (HxWxD): 14 × 107 × 61 cm
- Gross weight: 15,5 kg
- Product code: 467600
- EAN code: 3838942760341

