

DWC5926W

Professional dishwasher

General description

Turbo Drying Express™ ensures the dishes are dry and cool with combination of fan forced drying and fan assisted evacuation of moisture.

Product line: Professional Installation: Built-in Size: XI 820 mm Number of baskets: 2

Upper basket type: Exclusive - Basket wiring in steel, all pin rows foldable, divisble/foldable wine shelves, Light Lock™ for fastening lightweight items.

Lower basket type: Exclusive - Basket wiring in steel, all pin rows foldable, sliding tines in rear right, removable cutlery basket and vase/bottle holder for cleaning vases/baby bottles.

Panel colour: White

Construction & Performance

- 8 Steel $^{\text{TM}}$ Vital parts of the dishwasher made in stainless steel.
- No need to rinse the dishes thanks to Super Cleaning System™
- Automatic water-softener for better washing performance
- Number of spray arms: 2
- Number of spray zones: 8

Use & flexibility

- Number of baskets: 2
- Upper basket type: Exclusive Basket wiring in steel, all pin rows foldable, divisble/foldable wine shelves, Light Lock™ for fastening lightweight items.

 Lower basket type: Exclusive Basket wiring in steel, all pin rows foldable, sliding tines in rear right, removable cutlery basket and vase/bottle holder for cleaning vases/baby bottles.
- Interior light
- Illumination: Interior light
- Required inlet water pressure: 0,03-1 MPa

Interaction & Control

- Type of display: LCD display
- Number of programs: 16
- Number of options: 1
- Time remaining indicator: Time remaining indicator
- Wash end indication: Displayed with sound and light
- Available languages in control unit: DA, DE, EN, ES, FI, FR, IT, NL, NO, RU, SV

Programs

- 16 programmes: Quick; Intensive; Eco; Rinsing; Plastic; Universal; Universal plus; Wine glass; Beer glass; Pots and pans; Quick wash Sani; Drain; Program A; Program B; Program C; Universal sani
- Extra dry Improves the drying result

Design & integration

- Size 3/4" Can be connected to hot and cold water
- Height setting: 50 mm
- Possible adjustment of kick plate: 30 94/0 mm

Safety & Maintenance

- Aqua Safe™ system Multiple safety systems preventing water damages.
- Indication of low level of rinse-aid: Notification in display
- Salt refill indicator: Salt refill indicator

Technical data

- Size 3/4" Can be connected to hot and cold water
- Max. temperature of incoming water: 70 °C
- Connected load: 5800 W
- Fuse: 10 amp
- Frequency: 50 Hz
- Required inlet water pressure: 0,03-1 MPa
- Net weight: 53,6 kg

Dimensions

- Width: 596 mm
- Height: 820 mm Depth: 577 mm





- Maximum product height: 870 mm
- Length electrical cord: 1820 mm
- Length inlet hose: 168 cm
- Length outlet hose: 200 cm

Logistic information

- Packaging width: 640 mm
- Packaging height: 890 mmPackaging depth: 680 mm
- Gross weight: 56,9 kg
- Product code: 497744
- EAN code: 3838942062292





