

# **T411HD.W**

#### **General description**

T411HD.W

Product line: Logic Installation: Freestanding

Drying capacity: 1-11 kg

Number of programmes: 14

Energy class: A++

Type of dryer: Heat pump dryer

Type of display: LCD display

Anticrease Main colour: White

### **Construction & Performance**

- Long lasting stainless steel drum
- Durable brushless motor
- Heat pump
- Sensor and time controlled drying
- Drum volume: 145 l
- Butterfly drying system

### Use & flexibility

- Volume of container for condensed water: 6 I
- Removable filter
- Door diameter: 34 cm
- Door opening angle: 180 °
- Anticrease
- Time setting
- Humidity sensor
- Drum illumination: Yes

#### Interaction & Control

- Remaining time indication
- Type of display: LCD display
- End of programme sound signal
- Program memory
- Available languages in control unit: CZ, DA, DE, EN, ES, EE, FI, FR, HR, IT, JP, LT, LV, NL, NO, PL, RU, SK, SL, SV, ZH, ZH-CN

## **Programs**

- 14 programmes
- Auto dry
- Auto iron dry auto programme with some remaining moisture
- Auto terry for towels and bathrobes
- Auto jeans good for jeans and garment with thick seams
- Auto normal dry for thicker, non-sensitive cotton fabrics
- Auto down for down pillows, down jackets and other materials with down
- Auto synthetic for synthetics and other sensitive fabrics Timed drying
- Airing
- Bedding programme for bedding and other large items
- Refreshing programme for silk and wool
- Shirts lower temperature and slight remaining moisture to reduce wrinkles
- Quick Pro effective quick programme

# Design & integration

- Door opening: Reversible door opening
- Adjustable feet: 15 mm
- Loading position: Front

## Safety & Maintenance

- Lockable control panel
- Overheat protection
- Thermal and electonic protection against overheating

# Technical data

- Noise level: 65 dB(A)re 1 pW
- Power consumption in standby mode: 0,8 W



- Power consumption in off mode: 0,25 W
- Estimated annual energy consumption: 259,7 kWh
- Energy class: A++
- Grounded plug
- Plug type SHUKO
- Connected load: 700 W
- Number of phases: 1
- Fuse: 10 amp
- Frequency: 50 Hz
- Net weight: 60 kg
- ISO 14001

#### Dimensions

- Product dimensions (HxWxD):  $85 \times 59,5 \times 76,9$  cm
- Depth with door open: 1165 mm Length electrical cord: 2,1 m

# Logistic information

- Dimensions of packed product (HxWxD): 92  $\times$  64  $\times$  83,8 cm
- Gross weight: 64,6 kg
- Product code: 576824
- EAN code: 3838782011429



