



Fully Integrated Dishwasher

DFI644G

General description

Turbo Drying Express™ ensures the dishes are dry and cool with combination of fan forced drying and fan assisted evacuation of moisture.

Product line: Style

Installation: Fully integrated

Size: XL, 820 mm

Number of baskets: 3

Number of place settings (label): 14 place settings

Top tray: Easy height adjustment; Dividable and removable baskets in top rack; With rack for knives and utensils; With rack for bowls and cups; With telescopic rails; Handle

Upper basket type: Premium - Basket wiring in steel, fixed pin rows and foldable wine shelves.

Lower basket type: Premium - Basket wiring in steel, fixed pin rows and removable cutlery basket.

Handle with Stainless steel logotype

Removable cutlery basket for easy loading and unloading

Construction & Performance

- Extra durable stainless steel container.
- Aqua Detect™ - Instant recognition of any leakage in the motor compartment.
- Stand-by water protection - Leakage detection when machine is off.
- Anti Block™ - Self cleaning drain pump.
- 8 Steel™ - Vital parts of the dishwasher made in stainless steel.
- Hidden heater
- No need to rinse the dishes thanks to Super Cleaning System™
- Sensi Clean™ Sensor - measures dirtiness level
- Automatic water-softener for better washing performance
- Number of spray arms: 3
- Number of spray zones: 9
- Jet Spray™ - Extra dishwashing power for vases, bottles and baby bottles.
- Wide Spray™ - Extra dishwashing power for pots and pans
- Cutlery Spray™ - Extra dishwashing power for the cutlery basket

Use & flexibility

- Number of place settings (label): 14 place settings
- Number of baskets: 3
- Top tray: Easy height adjustment; Dividable and removable baskets in top rack; With rack for knives and utensils; With rack for bowls and cups; With telescopic rails; Handle
- Upper basket type: Premium - Basket wiring in steel, fixed pin rows and foldable wine shelves.
- Upper basket system: Easy height adjustable with lever
- Guide rails with ball bearings
- Lower basket type: Premium - Basket wiring in steel, fixed pin rows and removable cutlery basket.
- Small distance between the basket threads - makes loading easy and prevents small items to fall through.
- Removable cutlery basket for easy loading and unloading
- Required inlet water pressure: 0,03-1 MPa

Interaction & Control

- Type of display: LCD display
- Ability to create own programmes: Memory programme
- Number of programs: 13
- Number of options: 8
- Status Light™ - Visual indication of the dishwashing progress.
- Time remaining indicator: Time remaining indicator
- Wash end indication: Displayed with sound and light
- Available languages in control unit: DA, DE, EN, ES, EE, FI, FR, HR, IT, LT, LV, NL, NO, PL, PT, RU, SL, SV

Programs

- 13 Programs: Normal wash; Auto; Eco; Hygiene; Universal; Time program; Plastic; Rinse & hold; Upper half; Lower half; Crystal glass; Quick Pro; Self cleaning
- Delayed start: Possible to delay up to 24 hours
- Green mode - Less energy and water is used. The program time is extended.
- Speed mode - The program time is shortened. More energy is used.
- Night mode - Lower noise level. The program time is extended.
- Intensive mode - The dishwasher uses more heat and water. The program time is extended.
- Extra dry - Improves the drying result
- High temperature - For extra dirty dishes
- Super Rinse™ - Two extra rinses.

Design & integration

- From front adjustable rear foot

- Velcro strips for easy mounting and adjustment of the separate custom door
- Multifit outlet hose
- Integrated anti-siphon - Prevents spontaneous in- and outlet of water and simplifies elevated installation
- Custom door size 680-760mm
- Min. niche width: 600 mm
- Min. niche height: 820 mm
- Depth (incl. wall spacing): 560 mm
- Height setting: 50 mm

Safety & Maintenance

- Aqua Safe™ system - Multiple safety systems preventing water damages.
- Kid Safe™ - Lockable controls
- Indication of low level of rinse-aid: Notification in display
- Salt refill indicator: Salt refill indicator

Technical data

- Size 3/4" - Can be connected to hot and cold water
- Max. temperature of incoming water: 70 °C
- Plug type: Euro
- Connected load: 1900 W
- Number of phases: 1
- Fuse: 10 amp
- Frequency: 50 Hz
- Required inlet water pressure: 0,03-1 MPa
- Net weight: 48,2 kg
- Marked for recycling
- ISO 14001

Dimensions

- Width: 596 mm
- Height: 819 mm
- Depth: 559 mm
- Maximum product height: 869 mm
- Length electrical cord: 1825 mm
- Depth with door open: 1198 mm
- Length inlet hose: 163 cm
- Length outlet hose: 200 cm

Logistic information

- Packaging width: 640 mm
 - Packaging height: 890 mm
 - Packaging depth: 680 mm
 - Gross weight: 51,5 kg
 - Product code: 728541
 - EAN code: 3838782043345
-