



Induction hob

HIHM934M

General description

Main colour: Matt black ceramic glass
Capacity (Boost): 540 m³/h

4790 SFr.
Price (incl. VAT, excl. ARF)

A

Construction & Performance

- Soft cut hob edges
- Max capacity: 540 m³/h
- Max capacity recirculation mode: 410 m³/h
- Capacity power level 1: 95 m³/h
- Capacity power level 2: 189 m³/h
- Capacity power level 3: 322 m³/h
- Capacity (Boost): 540 m³/h
- Capacity recirculation (Boost): 410 m³/h
- Number of motors: 1
- Filter material: Stainless steel grease filter

Use & flexibility

- Number of Boost levels: 1
- Number of power levels: 5
- Number of speed positions: 5
- Coal filter code (optional as separate purchase): 0

Interaction & Control

- Electronic control
- Control setting: Touch control
- Timer function
- Grease filter indicator

Design & integration

- Easy install
- Flush installation
- Niche dimensions min-max (HxWxD): 49-52,6 × 84-87,4 × 15 cm

Safety & Maintenance

- SafeCall
- Washable grease filter
- Easy repair
- Overheat protection

Technical data

- Energy class: A
- Grease filtering efficiency class: A
- Fluid dynamic efficiency class: A
- Energy consumption in standby mode: 0,3 W
- Connected load: 7400 W
- Nominal current of fuse: 16 amp
- Max. noise level: 68 dB(A)re 1 pW

Dimensions

- Product dimensions (HxWxD): 15 × 87 × 52,2 cm
- Net weight: 22,5 kg

