



5-in-1 oven - Craft OCSM8478G

Type of display: Touch Screen Display
 Installation: Built-in
 Medium
 Main colour: Black ceramic glass
 Product dimensions (HxWxD): 45,5 x 59,5 x 54,6 cm
 Display Touch TFT, 5 Air Flow™ system, Pure steam system, Oven volume - 50 L, 5-in-1, AquaClean, Sous-vide, AutoRoast, Defrost, Eco

4990 SFr.
 Price (incl. VAT, excl. ARF)



**Display
Touch TFT**



**5 Air Flow™
system**



**Pure steam
system**



**Oven volume -
50 L**



5-in-1



AquaClean



Sous-vide



AutoRoast



Defrost



Eco



Construction & Performance

- SilverMatte
- Maximum oven temperature: 230 °C
- MultiSteam 360°
- Microwave power: 1000 W

Use & flexibility

- Interior lights (Illumination): Both sides
- Water container: 1,3 l
- Volume net (liter): 50 l
- Available baking levels: 4
- OpenView
- Wire guides
- 1 Premium grill rack
- 1 Glass tray
- 1 Full width steam tray non-perforated
- 1 Full width steam tray perforated
- 1 Shallow tray
- 1 pcs 1/2 width steam tray perforated
- 1 pcs 1/3 width steam tray perforated

Interaction & Control

- Knob shape: LED
- TFT display

Programs

- Lower heater BIO
- Upper heater
- Lower and upper heater
- Small infra heater
- Large infra heater
- Large infra heater with ventilaton
- Circular heater
- Eco function
- Lower heater and fan
- Lower heater with fan BIO
- Strong steam
- Medium steam
- Low steam
- Steam baking
- Direct steam injection
- Defrost
- WarmPlate
- FastPreheat
- STEPBake
- AutoRoast
- Microwaves and grill
- Microwave and hot air
- Microwaves

Standard accessories



FORS AG
 Schaftenholzweg 8
 2557 Studen BE
 Tel. 032 374 26 26, info@fors.ch

ASKO
 Inspired by Scandinavia

Design & integration

- Door material: Glass
- Main colour: Black ceramic glass
- Niche dimensions (HxWxD): 45 × 56 × 55 cm

Safety & Maintenance

- Dynamic oven cooling plus - DC+
- Door glass: Triple glazing with a protective grid
- SoftOpen and GentleClose door hinge
- ChildLock
- Mechanic door safety bolt
- Removable flat oven inner door glass surface
- AquaClean function
- Direct steam injection
- Descaling

Technical data

- Energy consumption in standby mode: 1 W
- Connected load: 3000 W
- Voltage (V): 220-240 V
- Nominal current: 16 amp
- Frequency: 50 Hz
- Number of phases: 1

Dimensions

- Product dimensions (HxWxD): 45,5 × 59,5 × 54,6 cm
- Length electrical cord: 1,5 m
- Net weight: 42,3 kg

Logistic information

- Dimensions of packed product (HxWxD): 55 × 66 × 70 cm
 - Gross weight: 47 kg
 - Product code: 731915
 - EAN code: 3838782152849
-

