

# WMC947PS



## General description

Product group: Professional washing machines  
Installation: Freestanding  
Loading capacity: 9 kg  
Spin speed: 1400 rpm  
17 programmes  
Energy class: A+++  
Main colour: Colour of stainless steel

## Programs

Standard Cotton 60°C  
Standard Cotton 40°C  
Heavy 90°C  
Heavy 60°C  
White wash 90°C  
White/Colour 60°C  
White/Colour 40°C  
Quick wash 60°C  
Quick wash 40°C  
Synthetic 40°C  
Wool/Hand 30°C  
Rinsing  
Microfibre 60°C  
Disinfection 40°C  
Disinfection 60°C  
Disinfection 90°C  
Allergy cotton 60°C

## Options

Adjustable spin speed: No  
Super wash

## Construction & Performance

Quattro Construction™ – vibration-free spinning  
Door: Smart Seal™  
Long lasting stainless steel drum  
Active Drum™ - for a careful yet effective wash cycle.  
Heater power: 7000 W  
Precise temperature control (max deviation: +/- 1 °C)  
Water level sensor  
Drum volume: 80 l

## Interaction & Control

Remaining time indicator  
Type of display: LCD display  
17 programmes

## Design & integration

Door opening: Hinge on left side  
Adjustable feet: 10 mm  
ASKO tumble dryer can be mounted on top of the washer  
Size 3/4" - Can be connected to hot and cold water  
Loading position: Front

## Safety & Maintenance

Removable lifters for easy cleaning  
Waterproof bottom plate  
Maximized water inlet time  
PEX inlet hose  
Anti Block™ - Self cleaning drain pump.  
Overflow protection  
Emergency door opening key  
Unbalance detection - protects the washer against harmful vibrations.  
Draining capacity: 20 l/min  
Overheat protection  
Thermal and electronic protection against overheating

## Technical data

G-factor: 530  
Water remaining after spin: 53 %  
Heater power: 7000 W  
Drum volume: 80 l

Drum volume (USA): 2,8 cu ft  
Brushless motor  
Payment system: Prepared  
Automatic Dosing System: Prepared external  
Shortest program time: 30 min  
Drain system: Pump

#### **Use & flexibility**

Easy close door  
Liquid detergent insert  
Temperature range: Cold-90°C  
Door diameter: 31 cm  
Door opening angle: 180 °

Size 3/4" - Can be connected to hot and cold water  
Counter weight material: Cast iron  
Counter weight (kg): 20,1 kg  
Noise level: 81 dB(A)re 1 pW  
Noise level washing: 59 dB(A)re 1 pW  
Estimated annual water consumption: 9020 l  
Power consumption in standby mode: 0,4 W  
Power consumption in off mode: 0,4 W  
Energy class: A+++  
Connected load: 7200 W  
Voltage (V): 400 V  
Number of phases: 3  
Fuse: 16 amp  
Frequency: 50 Hz  
Net weight: 94 kg  
ISO 14001

#### **Dimensions**

Product dimensions (HxWxD): 85 × 59,5 × 70 cm  
Adjustable feet: 10 mm  
Depth with door open: 1080 mm  
Length electrical cord: 1,8 m  
Length inlet hose: 150 cm  
Length outlet hose: 160 cm

#### **Logistic information**

Dimensions of packed product (HxWxD): 92 × 64 × 77,5 cm  
Gross weight: 96 kg  
Product code: 734492  
EAN code: 3838782330629  
Market: Professional