



# WMC6742V.T

## Professional washing machines

### General description

Product group: Professional washing machines  
Installation: Freestanding  
Loading capacity: 7 kg  
Spin speed: 1400 rpm  
25  
Main colour: Titanium

### Programs

- Heavy 90°C
- Heavy 60°C
- White wash 90°C
- White/Colour 60°C
- White/Colour 40°C
- Quick wash 60°C
- Quick wash 40°C
- Synthetic 40°C
- Wool/Hand 30°C
- Rinsing
- MOP 90°C
- MOP 60°C
- Microfibre 60°C
- Microfibre 40°C
- Disinfection 40°C
- Disinfection 60°C
- Disinfection 90°C
- Allergy cotton 60°C
- Allergy cotton 90°C
- Allergy synthetics 40°C
- Allergy synthetics 60°C
- Drum cleaning

### Options

- Adjustable spin speed: No
- Super wash

### Construction & Performance

- Quattro Construction™ – vibration-free spinning
- Door: Smart Seal™
- Long lasting stainless steel drum
- Active Drum™ - for a careful yet effective wash cycle.
- Heater power: 2000 W
- Precise temperature control (max deviation: +/- 1 °C)
- Water level sensor
- Drum volume: 60 l
- Drum volume (USA): 2,1 cu ft
- Brushless motor
- Shortest program time: 40 min
- Drain system: Valve

### Use & flexibility

- Easy close door
- Liquid detergent insert
- Temperature range: Cold-90°C
- Door diameter: 31 cm
- Door opening angle: 180 °

### Interaction & Control

- Up to 100 hours
- Remaining time indicator
- Type of display: LCD display
- 25
- Available languages in control unit: CZ, DA, DE, EN, ES, EE, FI, FR, HR, IT, JP, LT, LV, NL, NO,

#### Design & integration

- Door opening: Hinge on left side
  - Adjustable feet: 10 mm
  - ASKO tumble dryer can be mounted on top of the washer
  - Size 3/4" - Can be connected to hot and cold water
  - Loading position: Front
- 

#### Safety & Maintenance

- Removable lifters for easy cleaning
  - Maximized water inlet time
  - PEX inlet hose
  - Overflow protection
  - Emergency door opening key
  - Lockable control panel
  - Unbalance detection - protects the washer against harmful vibrations.
  - Draining capacity: 20 l/min
  - Overheat protection
  - Thermal and electronic protection against overheating
- 

#### Technical data

- G-factor: 530
  - Heater power: 2000 W
  - Drum volume: 60 l
  - Size 3/4" - Can be connected to hot and cold water
  - Counter weight material: Cast iron
  - Counter weight (kg): 10,4 kg
  - Connected load: 2200 W
  - Number of phases: 1
  - Fuse: 10 amp
  - Frequency: 50 Hz
  - Net weight: 77 kg
  - ISO 9001 certified manufacturer
  - ISO 14001
- 

#### Dimensions

- Product dimensions (HxWxD): 85 × 59,5 × 59,1 cm
  - Adjustable feet: 10 mm
  - Depth with door open: 965 mm
  - Length electrical cord: 2,1 m
  - Length inlet hose: 150 cm
  - Length outlet hose: 160 cm
- 

#### Logistic information

- Dimensions of packed product (HxWxD): 92 × 64 × 66,1 cm
  - Gross weight: 80,2 kg
  - Product code: 738279
  - EAN code: 3838782498800
  - Market: Professional
-

