



WMC8943PC.S

Professional washing machines

General description

Product group: Professional washing machines
Installation: Freestanding
Loading capacity: 9 kg
Spin speed: 1400 rpm
26 programs
Energy class: B
Main colour: Stainless Steel



Programs

- Heavy 90°C
- Heavy 60°C
- White wash 90°C
- White/Colour 60°C
- White/Colour 40°C
- Quick wash 60°C
- Quick wash 40°C
- Synthetic 40°C
- Wool/Hand 30°C
- Rinsing
- MOP 90°C
- MOP 60°C
- Microfibre 60°C
- Microfibre 40°C
- Disinfection 40°C
- Disinfection 60°C
- Disinfection 90°C
- Allergy cotton 60°C
- Allergy cotton 90°C
- Allergy synthetics 40°C
- Allergy synthetics 60°C
- Drum cleaning

Options

- Adjustable spin speed: No
- Super wash

Construction & Performance

- Quattro Construction™ – vibration-free spinning
- Door: Smart Seal™
- Long lasting stainless steel drum
- Active Drum™ - for a careful yet effective wash cycle.
- Heater power: 3000 W
- Precise temperature control (max deviation: +/- 1 °C)
- Water level sensor
- Drum volume: 80 l
- Drum volume (USA): 2,8 cu ft
- Brushless motor
- Payment system: Prepared
- Automatic Dosing System: Prepared external
- Shortest program time: 40 min
- Drain system: Pump

Use & flexibility

- Easy close door
- Liquid detergent insert
- Temperature range: Cold-90°C
- Door diameter: 31 cm
- Door opening angle: 180 °

Interaction & Control

- Up to 100 hours
- Remaining time indicator
- Type of display: LCD display

- 26 programs
- Available languages in control unit: CZ, DA, DE, EN, ES, EE, FI, FR, HR, IT, JP, LT, LV, NL, NO, PL, RU, SK, SL, SV, ZH, ZH-CN

Design & integration

- Door opening: Hinge on left side
- Adjustable feet: 10 mm
- ASKO tumble dryer can be mounted on top of the washer
- Size 3/4" - Can be connected to hot and cold water
- Loading position: Front

Safety & Maintenance

- Removable lifters for easy cleaning
- Maximized water inlet time
- PEX inlet hose
- Anti Block™ - Self cleaning drain pump.
- Overflow protection
- Emergency door opening key
- Lockable control panel
- Unbalance detection - protects the washer against harmful vibrations.
- Draining capacity: 20 l/min
- Overheat protection
- Thermal and electronic protection against overheating

Technical data

- G-factor: 530
- Spin drying efficiency class: B
- Moisture remaining: 49 / 49 / 49
- Heater power: 3000 W
- Drum volume: 80 l
- Size 3/4" - Can be connected to hot and cold water
- Counter weight material: Cast iron
- Counter weight (kg): 10,4 kg
- Noise level spinning: 75 dB(A)re 1 pW
- Noise spinning class: B
- Energy consumption per 100 cycles: 53 kWh
- Energy consumption per cycle for the Eco program 40–60 °C: 0,53 kWh
- Water consumption per cycle for the Eco program 40–60 °C: 41 l
- Consumption in off mode: 0,48 W
- Consumption in standby mode: 0,48 W
- Energy class: B
- Connected load: 3200 W
- Number of phases: 1
- Fuse: 16 amp
- Frequency: 50 Hz
- Net weight: 92 kg
- ISO 9001 certified manufacturer
- ISO 14001

Dimensions

- Product dimensions (HxWxD): 85 × 59,5 × 70,6 cm
- Adjustable feet: 10 mm
- Depth with door open: 965 mm
- Length electrical cord: 2,1 m
- Length inlet hose: 150 cm
- Length outlet hose: 160 cm

Logistic information

- Dimensions of packed product (HxWxD): 92 × 64 × 77,6 cm
 - Gross weight: 95,4 kg
 - Product code: 738294
 - EAN code: 3838782496752
 - Market: Professional
-

