



HIHD854GF

Induction hob with hood

General description

Main colour: Black ceramic glass

A

Construction & Performance

- 4 induction heating zones Left front: Ø 19×22 cm, 2,3/3,5 kW, Right front: Ø 19×22 cm, 2,3/3,7 kW, Left rear: Ø 19×22 cm, 2,3/3,5 kW, Right rear: Ø 19×22 cm, 2,3/3,7 kW
- Max capacity: 449 m³/h
- Max capacity recirculation mode: 491 m³/h
- Capacity power level 1: 214 m³/h
- Capacity power level 2: 328 m³/h
- Capacity power level 3: 399 m³/h
- Airflow boost position (PowerBoost 2) - extraction: 617 m³/h
- Airflow boost position (PowerBoost 2) - recirculation: 575 m³/h
- Number of motors: 2
- Power boost
- Filter material: Stainless steel grease filter

Use & flexibility

- Number of Boost levels: 1
- Number of power levels: 5
- Number of speed positions: 5
- Recirculation set number: 0
- Coal filter code (optional as separate purchase): 0

Interaction & Control

- Electronic control
- Control setting: Touch control
- Timer function
- Grease filter indicator

Design & integration

- Easy install
- Niche dimensions min-max (HxWxD): 49-52,4 × 78-83,4 × 19,9 cm

Safety & Maintenance

- Washable grease filter
- Easy repair
- Overheat protection

Technical data

- Energy class: A
- Grease filtering efficiency class: A
- Fluid dynamic efficiency class: A
- Energy consumption in standby mode: 0,48 W
- Connected load: 7200 W
- Max. noise level: 60 dB(A)re 1 pW

Dimensions

- Product dimensions (HxWxD): 19,6 × 83 × 52 cm
- Net weight: 24,3 kg

