



# DBI343ID.W.AU

## Built-in undercounter dishwasher

### General description

Turbo Combi Drying™  
Product line: Classic  
Installation type: Built under work top  
Size: XL, 82 cm  
Number of baskets: 2  
Number of place settings: 14 place settings  
Removable cutlery basket for easy unloading

### Construction & Performance

- Welded stainless steel container
- Exterior float
- Stand by water protection
- Anti-block drain pump
- 8 Steel™ construction
- Hidden heater
- SCS+ (Super Cleaning System+)
- Number of spray arms: 2
- Number of spray zones: 6
- Turbo Combi Drying™
- TotalDry – automatic door opening
- Cutlery Power Zone

### Use & Flexibility

- Number of place settings: 14 place settings
- Number of baskets: 2
- Dense basket wiring in both upper and lower basket
- Removable cutlery basket for easy unloading
- Required inlet water pressure: 0,03-1 MPa

### Interaction & Control

- Display type: LCD display
- Customizable programs: Program memory
- Number of programs: 9
- Number of options: 5
- Digital countdown indicator: Front Display
- Wash end indication: Visual and sound indication washing end

### Programs, options and modes

- Delayed start: Variable start delay up to 24 hours
- Speed mode
- Night mode
- Super rinse

### Design & Integration

- From front adjustable rear foot
- Simplified installation with integrated anti-siphon
- Min width: 600 mm
- Min height: 820 mm
- Depth (incl. wall spacing): 555 mm
- Height setting: 53 mm
- Kick plate adjustable depth: 30-94 mm

### Safety & Maintenance

- Aqua Safe™
- Kid Safe™ - panel
- Rinse-aid indication: Notification in display

### Technical data

- 3/4" Cold water connection
- Max. temperature of inflow water: 70 °C
- Noise level: 44 dB(A)re 1 pW
- Total cycle time of reference program (min): 168 min
- Estimated yearly energy consumption: 222 kWh
- Energy consumption reference program: 0,59 kWh
- Energy stars: 4

- Water stars: 5,5
- Water consumption: 10,1 l
- Consumption in standby mode: 0,78 W
- Plug type: Australia
- Connection rating: 2000 W
- Number of phases: 1
- Current: 10 amp
- Frequency: 50 Hz
- Required inlet water pressure: 0,03-1 MPa
- Net weight: 37,5 kg

#### Dimensions

- Width: 596 mm
- Height: 819 mm
- Depth: 554 mm
- Maximum product height: 872 mm
- Length electrical cord: 1730 mm
- Depth with door open: 1191 mm
- Length inlet hose: 163 cm
- Length outlet hose: 200 cm

#### Logistic information

- Packaging width: 640 mm
- Packaging height: 890 mm
- Packaging depth: 680 mm
- Gross weight: 40,8 kg
- Product code: 739996
- EAN code: 3838782622830
- Market: Domestic

